

SPRAY TEXTURE

Customer Service USA 1800 862 9022
www.panelrey.com

Manufacturer

Planta PANEL REY
Carretera Monterrey-Monclova km 11.5
El Carmen, NL. CP. 66560
Serafín Peña # 938 Sur C.P. 64000
Monterrey, Nuevo León. Phone: 1 800 862 9022

Description

Panel Rey® Spray Texture is a powder or ready-mix compound designed for application over most properly prepared interior surfaces. It is used to create a wide range of texture patterns using roller, brush, hopper-type gun or plastering spray pump machines.

Applications and uses

Panel Rey® Spray Texture can be applied with any tool or equipment for texturing. It is designed for most common patterns of texture. Add small portions of water and test the finish first. Follow the equipment directions and precautions. Texture must be dry before applying paint or any decoration. Do not apply when temperature of water, texture material or surfaces are below 50°F (10°C). Follow painting and decorating directions prescribed by appropriate manufacturers.

Advantages

- Spreads easily.
- Easy mixing
- Developed for different texture patterns.
- Prevents common undesired texture effects like pinholes, craters and lumps.

Limitations

- Spray Texture is specified for indoor application only.
- Spray Texture is not considered a finished surface.
- Sealing primer is required before or after texturing to avoid difference in sheen on wall and ceiling surface.
- Excess of water and/or excessive or high-speed mixing may cause cracking, poor bonding, abnormal shrinkage, craters and pinholes. Do not mix with any other wet or dry products.

Storage

Joint compounds and finishing products have a ten-month warranty, effective from the date of manufacture, and when stored under normal conditions, and in protected places. Do not stack more than two pallets high.

Greenguard Certified

Product certified for low chemical emissions.
UL.COM/GG UL 2818

Caution

Avoid dust from damp sanding. Use a mask and safety goggles. Dust resulting from sanding may irritate eyes, nose or throat. In the event of visual contact, thoroughly wash with water for 15 minutes until all particles are removed. If irritation persists, get medical attention. Do not ingest this product. KEEP OUT OF THE REACH OF CHILDREN. For more safety information refer to the SDS on Panel Rey's website.

Preparation

Surface must be dry, clean and free of oil, grease and soluble material. Apply a primer coat to equate the surface porosity/absorption to avoid differences in sheen. Mix the product with clean water until desired consistency, and make sure that the mixing equipment and container is clean to avoid contamination.

Composition

Vinyl acetate formulation with raw gypsum or limestone filler and additives. Contains No Asbestos.

General Application

DIRECTIONS FOR MIXING

POWDER

Slowly add one bag of dry powder texture (50 lb) to approximately 4 gal of clean water and mix to a heavy but lump-free consistency; then apply. Consistency can be adjusted by adding small amounts of water or Panel Rey Spray Texture.


READY-MIX

Add spray texture ready-mix into the spraying container then apply. If a different consistency is required add clean water for the desired texture pattern.

TECHNICAL REFERENCES

- ASTM C840: Standard Specification for Application and Finishing of Gypsum Board.
- GA-214: Gypsum Association publication "Levels of Gypsum Board Finish."
- GA-216: Gypsum Association publication "Recommended Specifications for the Application and Finishing of Gypsum Board."

SPRAY TEXTURE (POWDER)	SPRAY TEXTURE (READY MIX)
Coverage: 25 - 45 ft ² /lb	Coverage: 15 - 30 ft ² /lb
Packaging: Bag 50 Lb.	Packaging: Carton 2.5 Gal.



SUBMITTAL APPROVALS

Job Name _____
Contractor _____
Date _____

* For complete warranty details, visit www.panelrey.com

Stamps/Signatures