

# Side Supports

This structural piece is designed to be placed as a wind brace of the OMEGA system across a frame.

## Standards and Specifications

### CALIBER 24

SECTION	DIMENSION	TOLERANCE
Thickness	0.025 in	± 0.001 in
Galvanized	G - 40	≥ 0.40 oz/ft <sup>2</sup>
L Length (Nominal)**	25.00 m	± 2 mm
B Width	63.5 mm	+2 mm
T Thickness	0.025 in	± 0.001 in

\*\* Special lengths available to special order, restrictions apply.

### CALIBER 22

SECTION	DIMENSION	TOLERANCE
Thickness	0.030 in	± 0.001 in
Galvanized	G - 40	≥ 0.40 oz/ft <sup>2</sup>
L Length (Nominal)**	25.00 m	± 2 mm
B Width	63.5 mm	+2 mm
T Thickness	0.030 in	± 0.001 in

\*\* Special lengths available to special order, restrictions apply.

### CALIBER 20

SECTION	DIMENSION	TOLERANCE
Thickness	0.036 in	± 0.002 in
Galvanized	G - 60	≥ 0.60 oz/ft <sup>2</sup>
L Length (Nominal)**	25.00 m	± 2 mm
B Width	20.32 cm	+2 mm
T Thickness	28.01 cm	
	0.036 in	± 0.002

\*\* Special lengths available to special order, restrictions apply.

For more information contact us:

Customer Service USA  
1 800 862 9022

Phone  
+52 (81) 8345-0055

E-mail  
contact.us@gpromax.com

Web Site  
www.panelrey.com

