

Panel Rey[®] Join Reinforcement Tape

Panel Rey[®] Join Reinforcement Tape is designed to be used with the Panel Rey[®] construction system in the treatment and finishing of joints and corners of interior plaster panels so conceal and reinforce joints in walls and ceilings. This product is manufactured to meet Standard ASTM C-475 pursuant to the procedures of Standard ASTM C-474.

This product is made from high-quality paper fibers to provide the best-possible resistance. It is rough on both sides to increase its adherence to the surface, a center mark or easier folding and is the only tape with micro-perforations to make the paper embed better in the pastes of the Panel Rey[®] compounds.



Pack sizes available:

This is the paper tape packing looks like
WITH cardboard reinforcement.

Code	Description	Packing	Content
800195	Tape with cardboard reinforcement	76.25mts / 250'	20 pcs
800196	Tape with cardboard reinforcement	152.4mts / 500'	10 pcs

This is the paper tape packing looks like
WITHOUT box reinforcement.

Code	Description	Packing	Content
800752	Tape without cardboard reinforcement	76.15mts / 250'	20 pz
802430	Tape without cardboard reinforcement	152.4mts / 500'	10 pz



Application

The reinforcement tape should be placed in accordance with the ASTM C-840 installation recommendations. Panel Rey ® tape is applied in three simple steps.

1. First: Apply a thin layer of compound onto the surface and embed the tape on this product, ensuring the the edge of the mark is next to the surface. Leave approximately 1 mm of compound under the tape and eliminate the excess.

2. Second: Allow the compound to dry and apply and second and third payer of compound, making the first layer fade and increasing the width of the application by 2" (5 cm) o each side. Make sure the edges fade correctly and if necessary, roughen the dried compound before applying the second and third layers.

3. Third: Allow to dry fully and roughen to achieve the desired finish. Refer to the Recommended Finishing Levels provided by Gypsum Association Bulletin GA-214-97. To paint or decorate, follow the instructions of the manufacturer of the material to be used. Make sure that the surfaces are clean, dry and free of dust, oil or grease.

Advantages

- Paper manufactured from entwined virgin fibers for maximum resistance.
- Ensures the rupture values are met for Dry and Damp Tension.
- Enables heavy-duty use, withstanding normal wear and tear during application.
- Rough surfaces and micro-perforations.
- Marked edges to facilitate folding in internal and external corners.
- Rolled in cardboard centers for easier handling during application.

Product Data

- 2" (5.2 cm)-wide paper tape rolls
- 76.25mt / 250´ and 152.4mt / 500´ lengths
- Two pack sizes: box of 20 rolls and box of 10 rolls.

For more information contact us:

Customer Service USA
1 800 862 9022

Phone
+52 (81) 8345-0055

E-mail
contact.us@gpromax.com

Web Site
www.panelrey.com

